



Only suitable for well insulated areas and not designed to be the primary heat source

2.8KW ELECTRIC FAN HEATER (110V)

MODEL NO: DEVIL 3003-B

PART NO: 6925126

OPERATION & MAINTENANCE INSTRUCTIONS



ORIGINAL INSTRUCTIONS

DL0525 Rev 2

INTRODUCTION

Thank you for purchasing this CLARKE product.

Before attempting to use this product, read this manual carefully. In doing so you guarantee the safety of yourself and that of others around you, and you can look forward to your purchase giving you long and satisfactory service

GUARANTEE

This product is guaranteed against faulty manufacture for a period of 12 months from the date of purchase. Please keep your receipt as proof of purchase.

This guarantee is invalid if the product is found to have been abused, tampered with, or not used for the purpose for which it was intended. Faulty goods must be returned to their place of purchase, no product can be returned to us without prior permission.

This guarantee does not effect your statutory rights.

FUNCTION AND OPERATING PARAMETERS

This is a forced air heater. It's intended use is for drying and the warming of commercial/industrial buildings and construction sites and areas where adequate ventilation is provided.

- It must be operated as prescribed in the operating manual.
- It is not intended to be used for domestic use or for the heating of habitable areas.
- It is not intended to be used to reach and maintain a certain level of human thermal comfort within an enclosed space in which the heater is situated.
- It is not intended to be used in enclosed areas with restricted ventilation.
- It is not intended for warming animals or live stock.

THE FOLLOWING TABLE ADDRESSES THE INFORMATION REQUIREMENTS OF REG.2024/1103

Item	Symbol	Value	Unit		
Heat output					
Nominal heat output	P _{nom}	2.800	kW		
Minimum heat output (indicative)	P _{min}	1.400	kW		
Maximum continuous heat output	P _{max, c}	2.800	kW		
Auxiliary electricity consumption					
In off mode	Po	0.000	W		
In standby mode	P _{sm}	0.000	W		
In idle mode	P _{idle}	0.000	W		
In network standby	P _{nsm}	0.000	W		
Seasonal space heating energy efficiency in active mode	n _{s, on}	85	%		
Standby mode with display information or status	-	No	-		
Type of heat output/room temperature control (sele	ect one)				
Single stage heat output, no temperature control					
Two or more manual stages, no temperature control			No		
With mechanical thermostat temp control			Yes		
With electronic temperature control					
Electronic temperature control with day timer					
Electronic temperature control with week timer					
Other control options (multiple selections possible)					
Room temperature control with presence detection			No		
Room temperature control with open window detection					
Room temperature control with distance control option					
Room temperature control with adaptive start control			No		
Room temperature control with working time limitation					
Room temperature control with black bulb sensor			No		
Room temperature control with self-learning functionality			No		
Room temperature control with control accuracy			No		

SAFETY RULES

Make sure that you read, understand and comply with the following guidance. These safety symbols should appear on the heater.



Hot Surface, Do Not Touch



Read the manual



Do Not Cover

GENERAL

- **DO NOT** operate the heater when you are tired or under the influence of alcohol, drugs or intoxicating medication.
- DO NOT stand on the heater.
- **DO NOT** use if dropped. **DO NOT** use if there is visible signs of damage.
- DO NOT use the heater with wet hands or when there is water on the power cable.
- Turn the heater off when not in use and keep it in a safe, dry, childproof location.
- The heater is designed to heat enclosed areas such as workshops and other industrial areas. **DO NOT** use the heater for any other function. It is not suitable for drying clothes or laundry.
- This heat can be used by children aged 8 and above and persons with reduced physical, sensory and mental capabilities or lack of knowledge if they have been given instruction concerning the use of the appliance in a safe way and understand the hazards.
- Children of less than 3 years should be kept away unless continuously supervised.

ELECTRICAL SAFETY



WARNING: THIS HEATER MUST BE EARTHED AND IS ONLY FOR USE WITH A 110VOLT SUPPLY.

- Regularly inspect the power cable / plugs for damage/looseness. **DO NOT** use the heater it the power cable is damaged.
- Minimise the risk of electric shock by installing a RCCB (Residual Current Circuit Breaker) and a suitable isolator into the main distribution board.

- Make sure that the voltage on the rating label is the same as the voltage of the power supply. If in doubt, consult a qualified electrician.
- DO NOT abuse the electrical cable. DO NOT use the cable for pulling or unplugging the heater.
- Keep the cable away from sources of heat, oil, sharp edges or moving parts.
 Damaged or tangled cables increase the risk of electric shock.
- **DO NOT** use extension cables with this heater.

POSITIONING



WARNING: DO NOT USE THE HEATER NEAR FLAMMABLE MATERIAL, LIQUIDS, SOLIDS, GASES OR COMPRESSED GAS CYLINDERS ETC.

- This heater is designed for indoor use only.
- **DO NOT** use this heater in small rooms when they are occupied by persons not capable of leaving the room on their own, unless constant supervision is provided.
- **DO NOT** place the heater close to a bath, wash basin, shower, swimming pool or any other water-filled area or wet surface. **DO NOT** place the heater against any surface such as a wall, door or furniture etc.
- DO NOT place the heater immediately below any electrical outlet.
- **NEVER** place the heater near textiles, curtains or combustible materials etc. Allow 2 metres clearance all round this heater.
- **DO NOT** place the heater on a raised surface or anywhere it could topple over. **ONLY** use this heater on a horizontal and stable surface.
- Take care to ensure that the grille cannot be blocked.
- DO NOT operate fan heater in explosive atmospheres such as in the presence of flammable liquids, gases or dust such as in a paint spray booth, or any explosive environment. Electric motors create sparks which may ignite dust or fumes.

OPERATION

- The heater must only be used by people who have read these instructions and have been trained in its use.
- **DO NOT** obstruct the air inlet and outlet sections of the heater.
- DO NOT cover the heater.
- **DO NOT** touch the heater casing or grille when first switched off, as these will be very hot and will take time to cool.

- **DO NOT** get the heater wet or use in areas of high condensation.
- DO NOT allow the power lead to touch hot surfaces.
- **DO NOT** connect other appliances to the same mains socket as the heater.
- **DO NOT** use this heater with a programmable timer used to switch it on automatically.
- **CAUTION:** Some parts of this product can become very hot and cause burns. Particular attention should be given where children, vulnerable people and animals are present.

SPECIFICATIONS

Operating Voltage / Frequency	110V / 50Hz	
Maximum output	output 2.8kW (2 x elements 1.4kW	
Temperature Setting Range	0 to +40°C	
Input Wattage:		
Fan only	0.04 kW	
Heat Setting 1	1.4 kW	
Heat Setting 2	2.8 kW	
Required Power	25.5A	
Max Air Output	570 m ³ /h	
Safety Devices	Thermal cut-out	
Ingress Protection	IPX0	
Duty cycle	S1-continuous	
Depth x Width x Height	255 x 255 x 390 mm	
Weight 4.6 kg		

ELECTRICAL CONNECTIONS



WARNING: READ THESE ELECTRICAL SAFETY INSTRUCTIONS THOROUGHLY BEFORE CONNECTING THE HEATER TO THE POWER SUPPLY.

This heater MUST be connected to a 110 Volt, 1 phase 50Hz supply through a suitably fused isolator switch. ON NO ACCOUNT MUST A 230V, 13AMP (BS1363) PLUG BE USED.

If the plug has to be changed because it is not suitable for your socket, or because of damage, it must be removed and a replacement fitted, following the wiring instructions shown below. The old plug must be discarded safely, as insertion into a power socket could cause an electrical hazard.



WARNING: THE WIRES IN THE POWER CABLE OF THIS PRODUCT ARE COLOURED IN ACCORDANCE WITH THE FOLLOWING CODE:

BLUE = NEUTRAL BROWN = LIVE YELLOW AND GREEN = EARTH

If the colours of the wires in the power cable do not agree with the markings on the plug.

- The BLUE wire must be connected to the terminal marked N or coloured black.
- The BROWN wire must be connected to the terminal marked L or coloured red.
- The YELLOW AND GREEN wire must be connected to the terminal marked E or or coloured gi(1).

We strongly recommend that this machine is connected to the mains supply through a RCCB (Residual Current Circuit Breaker).

NOTE: If a portable 110V transformer is used, make sure it has a rated capacity sufficient to take the load of the heater.

In the event that the heater is hard wired into the electrical system, it must be carried out in accordance with IEE regulations.

Any power supply provided by the user must be comparable with the power cable supplied with the heater, and any additional cables should not be allowed to cause a trip hazard.

If in any doubt, consult a qualified electrician. **DO NOT** attempt any electrical repairs yourself.

OPERATION




WARNING: DO NOT USE THIS HEATER IN SMALL ROOMS IF OCCUPIED BY PERSONS NOT CAPABLE OF LEAVING THE ROOM ON THEIR OWN UNLESS CONSTANT SUPERVISION IS PROVIDED.




CAUTION: SOME PARTS OF THIS PRODUCT CAN BECOME VERY HOT AND CAUSE BURNS. PARTICULAR ATTENTION HAS TO BE GIVEN WHERE CHILDREN AND VULNERABLE PEOPLE ARE PRESENT.

- 1. Put the heater in a level position on a flat surface and at a safe distance from flammable materials. Keep a minimum of 2m clearance all round.
- 2. Connect the heater to a suitable 110V power supply.
- 3. Set the thermostat control to the maximum setting (fully clockwise).
- 4. Set the mode selector to one of the 3 settings:

0	Off
*	Fan only
*=	Fan + Heat Setting 1
*=	Fan + Heat Setting 2





- 5. Once the room reaches the required temperature, turn the thermostat control slowly counter-clockwise until the thermostat clicks. Leave the control in this position.
 - The room temperature will be maintained at this setting. The heater will continue to operate until the power switch is turned to the OFF position.

6. When not in use, disconnect the heater from the power supply. Store it in a safe, dry, childproof location.

SAFETY DEVICE

This heater is fitted with a thermal cut-out safety device which prevents the unit overheating.

If the thermal cut-out device is actuated, the heating elements will switch off and the fan with continue to run to cool the unit.

Allow time for the unit to cool (10 mins) before manually re-setting.

To re-set, firmly press the button located on the front panel using a suitable tool.



MAINTENANCE



WARNING: ALWAYS DISCONNECT FROM THE POWER SUPPLY AND ALLOW THE HEATER IT TO COOL DOWN BEFORE PERFORMING ANY MAINTENANCE TASKS.

- Clean the heater with a soft damp cloth, DO NOT use solvents or abrasives.
- Check that the heater is in good working order. Take immediate action to have any damaged parts repaired or replaced by the Clarke service department.
- **DO NOT** allow the heating elements to become covered with dust which could become a fire hazard. If used in a dusty workplace it should be cleaned as described under Maintenance on page 9.
- Only recommended parts should be used. Unapproved parts may be dangerous and will invalidate the warranty.
- Have your heater repaired by a qualified person using identical replacement parts. This will ensure that the safety of the heater is maintained.

FAULT FINDING

Problem	Possible Cause	Remedy
Heater does not operate, although plugged in with the selector switch and thermostat switched on.	Plug is loose/bad connection.	Pull the plug out & check the connection of the plug and socket.
	Fuse blown or circuit breaker has tripped.	Replace if necessary and investigate cause. If fuse blows repeatedly, consult your Clarke dealer.
	No power at socket outlet.	Insert the plug in a functioning socket.
Heating element glowing hot.	Input voltage too high.	Use a power supply in accordance with the rating on the product label.
	Air inlet grille is blocked.	Ensure the heater is kept away from any objects which could cover the air inlet or be drawn into it.
Heater has failed to heat up so only the air fan has operated.	Thermostat has tripped.	Turn the thermostat and listen. If there is no CLICK and the thermostat is not damaged, the heater will automatically switch ON when it has cooled down.
Abnormal noise.	Heater is not level.	Stand the heater on a level surface.

ENVIRONMENTAL RECYCLING POLICY



Through purchase of this product, the customer is taking on the obligation to deal with the WEEE in accordance with the WEEE regulations in relation to the treatment, recycling & recovery and environmentally sound disposal of the WEEE.

In effect, this means that this product must not be discarded with general household waste. It must be discarded according to the laws governing Waste Electrical and Electronic Equipment (WEEE) at a recognised disposal facility.

DECLARATIONS OF CONFORMITY





Hemnall Street, Epping, Essex, CM16 4LG

DECLARATION OF CONFORMITY

This is an important document and should be retained.

We hereby declare that this product(s) complies with the following legislation:

Low Voltage Directive Electromagnetic Compatibility Directive

2014/35/EU 2014/30/EU 2009/125/EC

Ecodesign Directive

2011/65/EU

Restriction of Hazardous Substances (RoHS) Directive

The following standards have been applied to the product(s):

aforementioned legislation has been compiled and is available for inspection by the relevant enforcement The technical documentation required to demonstrate that the product(s) meet(s) the requirement(s) of the EN IEC 62321-2:2021, EN IEC 55014-2:2021, EN 62321-1:2013, EN 62321-6:2015, EN 62233:2008 EN 60335-2-30:2009/A13:2022, EN 61000-3-3:2013/A2:2021, EN 62321-3-1:2014, EN 62321-5:2014 EN 62321-7-2:2017, EN 50564:2011 EN 60675:1995+A1:1998+A2:2018+A11:2019, EN IEC 61000-3-2:2019/A2:2024, EN 62321-8:2017, EN 60335-1:2012/A16:2023, EN 62321-4:2014/A1:2017, EN IEC 55014-1:2021, EN 62321-7-1:2015

The UKCA mark was first applied in: 2023

DEVIL 3003-B

Electric Space Heate

Refer to product/packaging label

28/04/2025

Date of Issue: Serial/Batch Number: Model Number(s): Product Description

Signed

J.A Clarke

Director

DEVIL 3003-B UKCA Clarke DOC 042825

Page 1 of 1

DEVIL 3003-B CE Clarke DOC 042825



This is an important document and should be retained. **DECLARATION OF CONFORMITY**

We hereby declare that this product(s) complies with the following legislation:

2014/30/EU 2009/125/EC Ecodesign Directive

Electromagnetic Compatibility Directive Low Voltage Directive

2011/65/EU 2014/35/EU

Restriction of Hazardous Substances (RoHS) Directive

The following standards have been applied to the product(s):

EN 62321-7-2:2017, EN 50564:2011 EN 60675:1995+A1:1998+A2:2018+A11:2019, EN IEC 61000-3-2:2019/A2:2024, EN 62321-8:2017, EN IEC 62321-2:2021, EN IEC 55014-2:2021, EN 62321-1:2013, EN 62321-6:2015, EN 62233:2008 EN 60335-1:2012/A16:2023, EN 62321-4:2014/A1:2017, EN IEC 55014-1:2021, EN 62321-7-1:2015 EN 60335-2-30:2009/A13:2022, EN 61000-3-3:2013/A2:2021, EN 62321-3-1:2014, EN 62321-5:2014

The technical documentation required to demonstrate that the product(s) meet(s) the requirement(s) of the aforementioned legislation has been compiled and is available for inspection by the relevant enforcement

The CE mark was first applied in: 2023

Model Number(s): Product Description: Electric Space Heater

DEVIL 3003-B

Refer to product/packaging label

28/04/2025

Date of Issue: Serial/Batch Number:

Signed:

J.A Clarke

Director

Page 1 of 1

A SELECTION FROM THE VAST RANGE OF





AIR COMPRESSORS

From DIY to industrial, Plus air tools, spray guns and accessories.

GENERATORS

Prime duty or emergency standby for business, home and leisure.

POWER WASHERS

Hot and cold, electric and engine driven - we have what you need

WELDERS

Mig, Arc, Tig and Spot. From DIY to auto/industrial.

METALWORKING

Drills, grinders and saws for DIY and professional use.

WOODWORKING

Saws, sanders, lathes, mortisers and dust extraction.

HYDRAULICS

Cranes, body repair kits, transmission jacks for all types of workshop use.

WATER PUMPS

Submersible, electric and engine driven for DIY, agriculture and industry.

POWER TOOLS

Angle grinders, cordless drill sets, saws and sanders.

STARTERS/CHARGERS

All sizes for car and commercial use.



PARTS & SERVICE: 0208 988 7400

Parts Enquiries
Parts@clarkeinternational.com

Servicing & Technical Enquiries
Service@clarkeinternational.com

SALES: UK 01992 565333 or Export 00 44 (0)1992 565335

CIAPE INTERNATIONAL Hemnall Street, Epping, Essex CM16 4LG www.clarkeinternational.com